



**1. COMPANY AND PRODUCT IDENTIFICATION**

**iLoveToCreate**  
 A Duncan Enterprises Company  
 5673 East Shields Avenue  
 Fresno, CA 93727  
 559-291-4444  
 559-291-9444 (Fax)

**EMERGENCY TELEPHONE NUMBERS**  
**Health Emergencies:**  
 559-291-4444 7:00 am – 3:30 pm Pacific Std. Time  
**Spill and Off-Hour Health Emergencies:**  
 800-424-9300 U.S. and Canada  
 703-527-3887 Outside U.S. and Canada (Collect)

**Product Name:** ALEENE'S CRYSTAL CLEAR TACKY SPRAY  
**Product Category:** Solvent - Based Aerosol Adhesive

**2. HAZARDS IDENTIFICATION**

HMIS Hazard Ratings for Product		Rating Scale:
Health	2	0 = Minimal
Flammability	4	1 = Slight
Reactivity	1	2 = Moderate
Personal Protection	See Section 8	3 = Serious
		4 = Severe
		* = Chronic Effects

**EMERGENCY OVERVIEW**  
 Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

**Effects of Overexposure:**

<b>Eye Contact:</b>	Can cause severe irritation, redness, tearing, blurred vision
<b>Skin Contact:</b>	Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis
<b>Inhalation:</b>	Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Overexposure may cause damage to the nervous system. Possible cardiac arrhythmias at high concentrations.
<b>Ingestion:</b>	No information available
<b>Chronic Hazards:</b>	Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage
<b>Primary Route(s) of entry:</b>	Eye contact, Skin Contact, Skin Absorption, Inhalation

## iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Weight %	TLV-TWA ppm	TLV-STEL ppm	PEL-TWA ppm	PEL-CEILING ppm	Company TLV-TWA ppm	SKIN
Hexane	110-54-3	<35.0	50	N.E.	500	N.E.	N.E.	NO
Acetone	67-64-1	<20.0	500	750	1,000	N.E.	N.E.	NO
Isobutane	75-28-5	<15.0	N.E.	N.E.	N.E.	N.E.	1,000	NO
Propane	74-98-6	<10.0	2,500	N.E.	1,000	N.E.	N.E.	NO
Dimethyl Ether	115-10-6	<10.0	N.E.	N.E.	N.E.	N.E.	1,000	NO

For explanation of abbreviations, see Section 16.

### 4. FIRST AID MEASURES

<b>Eye Contact:</b>	Flush eyes with large amounts of water, lifting upper and lower eyelids occasionally. Get medical attention.
<b>Skin Contact:</b>	Wash affected areas thoroughly with soap and water. Remove contaminated clothing and launder before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, makeup remover, mineral spirits, or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.
<b>Inhalation:</b>	Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

### 5. FIRE FIGHTING MEASURES

<b>Flash Point:</b>	- 156 F (Pensky-Martens Closed Cup Method)
<b>Lower Explosive Limit:</b>	1.0%
<b>Upper Explosive Limit:</b>	18.0%
<b>Autoignition Temperature:</b>	N.D.
<b>Extinguishing Media:</b>	CO <sub>2</sub> , Dry Chemical, Foam, or Water Fog

<b>Unusual Fire And Explosion Hazards:</b>	Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol products – exposure to temperatures over 130 F may cause containers to burst releasing highly flammable gas.
<b>Special Fire Fighting Procedures:</b>	Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Steps to be Taken in Case Material is Released or Spilled</b>	Eliminate sources of ignition and ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source and prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper container for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.
--	---

## iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray

### 7. HANDLING AND STORAGE

**Handling**

Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

**Storage**

Do not store above 120 F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition.

### 8. EXPOSURE CONTROL AND PERSONAL PROTECTION

<b>Engineering Controls:</b>	Provide sufficient mechanical ventilation (general and/or local exhaust) to maintain exposure below TLV(s).
<b>Respiratory Protection:</b>	If work place exposure limits of product or any component are exceeded, use a NIOSH/MSHA approved respirator. Consult your safety equipment supplier for recommendations.
<b>Skin Protection:</b>	Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations.
<b>Eye Protection:</b>	Wear safety glasses at minimum; more extensive protection may be necessary depending on how the product is to be used.
<b>Other Protective Equipment:</b>	Wear impervious clothing if bodily exposure is anticipated. Consult your safety supply vendor for recommendations.
<b>Hygienic Practices:</b>	Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Boiling Range:</b>	-44 – 159 F	<b>Vapor Density:</b>	Heavier than air
<b>Odor:</b>	Mint when wet	<b>Odor Threshold:</b>	N.D.
<b>Appearance:</b>	Light Amber	<b>Evaporation Rate:</b>	Faster than butyl acetate
<b>Solubility in Water:</b>	Negligible	<b>Specific Gravity:</b>	0.7138
<b>Freeze Point:</b>	N.D.	<b>pH:</b>	N.A.
<b>Vapor Pressure:</b>	N.D.	<b>Viscosity</b>	N.D.
<b>Physical State:</b>	Liquid	<b>VOC Product:</b>	445 g/l
<b>Coefficient of Water / Oil Distribution:</b>	N.D.	<b>VOC Less Exempt Solvents (Acetone)</b>	516 g/l

For explanation of abbreviations, see Section 16.

### 10. STABILITY AND REACTIVITY

<b>Conditions to Avoid:</b>	Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.
<b>Incompatibilities:</b>	Oxidizing agents, acids, reducing agents, strong oxidizers
<b>Hazardous Decomposition Products:</b>	carbon monoxide and carbon dioxide, various hydrocarbons, sulfur dioxide, sulfur monoxide
<b>Hazardous Polymerization:</b>	will not occur under normal conditions
<b>Stability:</b>	This product is stable under normal storage conditions

## iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray

### 11. TOXICOLOGICAL INFORMATION

#### Effects of Overexposure - Acute

<b>Eye Contact:</b>	Can cause severe irritation, redness, tearing, blurred vision
<b>Skin Contact:</b>	Prolonged or repeated contact can cause moderate irritation, defatting, dermatitis
<b>Inhalation:</b>	Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Overexposure may cause damage to the nervous system.
<b>Ingestion:</b>	No information available

#### Effects of Overexposure – Chronic

Overexposure to this material (or its components) has been found to cause the following effects in laboratory animals: damage to the kidney, eye, liver, lung, nasal cavity, nervous system, and testes  
Overexposure to this material (or its components) has been found to cause the following effects in humans: visual impairment and central nervous system effects

### 12. ECOLOGICAL INFORMATION

No data available

### 13. DISPOSAL CONSIDERATIONS

#### Waste Disposal Method

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Do not incinerate. Depressurize container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

### 14. TRANSPORT INFORMATION

#### U.S. Department of Transportation Information

<b>DOT Proper Shipping Name:</b>	Aerosols
<b>DOT Hazard Class:</b>	2.1
<b>Hazard Subclass:</b>	None
<b>DOT UN/NA Number:</b>	UN1950

<b>Packing Group:</b>	None
<b>RESP. Guide Page:</b>	126

#### Additional Information:

For domestic ground and air shipment this product may be shipped as a Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D AIR designation.

**iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray**

**15. REGULATORY INFORMATION**

**U.S. Federal Regulations:**

**OSHA:** Hazardous by definition of Hazard Communication Standard 29 CFR 1910.1200

**CERCLA – SARA Hazard Category:**

This product has been reviewed according to the EPA “Hazard Categories” promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

**Immediate Health Hazard, Chronic Health Hazard, Fire Hazard, Pressurized Gas Hazard**

**SARA Section 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Percent by Weight</b>
Hexane	110-54-3	<25

Hexane is a mixture of n-hexane and other compounds all falling under the general chemical name light hydrotreated distillate CAS-68410-97-9. The n-hexane content in this product is below 25%. On June 30, 1993, the OSHA Z-1-A Table was revoked and OSHA reverted back to their prior exposure limits. The values on this SDS reflect the roll back to the prior values. Some states may continue to enforce the 1993 limits. On June 16, 1995, EPA announced in a final rule that acetone would no longer be considered a VOC for air attainment standards. It is now an exempt compound. The June 16 rule also removed acetone from the list of SARA 313 reportable chemicals.

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States.

<b>Chemical Name</b>	<b>CAS Number</b>
No Information Available	

**International Regulations**

**Canadian WHMIS Class:** No Information Available



Products bearing the Caution Label are certified to be properly labeled in a program of toxicological evaluation by a nationally recognized toxicologist. The products are certified by the toxicologist to be labeled in accordance with the chronic hazard labeling standard ASTM D-4236.

**iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray**

**16. OTHER INFORMATION**

<b>Table of Abbreviations</b>	
<b>ACGIH</b>	American Conference of Governmental Industrial Hygienists
<b>ANSI</b>	American National Standards Institute
<b>ASTM</b>	American Society for Testing Materials
<b>°C</b>	Degrees Centigrade
<b>CAS</b>	Chemical Abstract Service
<b>CERCLA</b>	Comprehensive Environmental Response, Compensation and Liability Act
<b>CFR</b>	Code of Federal Regulations
<b>CPR</b>	Controlled Products Regulations
<b>DOT</b>	Department of Transportation
<b>EPA</b>	Environmental Protection Agency
<b>°F</b>	Degrees Fahrenheit
<b>FDA</b>	Food & Drug Administration
<b>g / l</b>	Grams per liter
<b>DOT</b>	Department of Transportation
<b>EPA</b>	Environmental Protection Agency
<b>°F</b>	Degrees Fahrenheit
<b>FDA</b>	Food & Drug Administration
<b>g / l</b>	Grams per liter
<b>Hg</b>	Mercury
<b>HMIS</b>	Hazardous Materials Identification System
<b>IARC</b>	International Agency for Research on Cancer
<b>LD</b>	Lethal Dose
<b>mg / kg</b>	Milligram per kilogram
<b>mm</b>	Millimeter
<b>SDS</b>	Safety Data Sheet
<b>MSHA</b>	Mine Safety and Health Administration
<b>N.A.</b>	Not Applicable
<b>N.D.</b>	Not Determined
<b>N.E.</b>	Not Established
<b>NFPA</b>	National Fire Protection Association
<b>NIOSH</b>	National Institute for Occupational Safety and Health
<b>NTP</b>	National Toxicology Program
<b>OSHA</b>	Occupational Safety and Health Administration
<b>ppm</b>	Parts per million
<b>SARA</b>	Superfund Amendment and Reauthorization Act
<b>STEL</b>	Short-Term Exposure Limit
<b>TSCA</b>	Toxic Substances Control Act
<b>TWA</b>	Time - Weighted Average
<b>U.N.</b>	United Nations
<b>WHMIS</b>	Workplace Hazardous Materials Information System
<b>&gt;</b>	Greater Than
<b>&lt;</b>	Less Than

**iLoveToCreate Safety Data Sheet – Aleene’s Crystal Clear Tacky Spray**

**OTHER INFORMATION (Continued)**

<b>Creation Date:</b>	04/12/07
<b>Revision Date:</b>	01/17/13
<b>Technical Contact:</b>	Frank Peters Research & Development Manager iLoveToCreate A Duncan Enterprises Company 5673 East Shields Avenue Fresno, CA 93727 559-291-4444 559-291-9444 (Fax)

**Disclaimer**

The information given and the recommendations made herein apply to our product(s) alone and not combined with any other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. No guarantee of accuracy is made. It is the purchaser’s responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.